


Balcony curtain profile for embedding in concrete




Aluminium, grey, RAL 7038


Aluminium, white, RAL 9016

Stock lengths of 6 m

Accessories



Installation accessories



Services

Made-to-measure

Bending service

Plan view (seen from above). State room side.





Radii: from 300 mm  
90° angle or angle of your choice



Non-standard radii and angles as per sketch

Installation instructions, see next page


Installation




1. Treat the curtain profile HM-20110 (HM-20115) with silicone spray.



2. Insert movable protective tape into the curve of the curtain profile.




3. The protective strip should reach approx. 10 cm into the straight.




4. Mark the side of the strip end.




5. Seal the curtain profile with the side cap 21052 (HM-20115 with 21053) (to prevent the ingress of concrete water).




6. Adjust curtain profile to marking and mark tape end on panel.




7. Remove the curtain profile once more.




8. Fix pre-drilled installation strips to marking with Hamotec special nails.



9. Clip the curtain profile onto the installation strip.




10. Drill two side holes into the curve of the profile.




11. Fix the curtain profile to the panel using aluminium nails.



12. Concrete in the profile.



13. Remove the panel once hardened.




14. Remove the remaining protective strip.

**Caution:**

It is **essential** that you re-insert the protective strip if the ceiling still needs to be painted or use another means to protect it!

Article description	Order no.
---------------------	-----------



**Balcony curtain profile for embedding in concrete**  
for curtain fabrics and tarpaulin as privacy  
and sun screen

Aluminium, grey, RAL 7038

20110.11


Aluminium, white, RAL 9016

20110.20



Stock lengths of 6 m

Made-to-measure + 20%




**Cover strip L110, white plastic**  
drilled 2.0 mm

21049.20



Stock lengths of 6 m

Made-to-measure + 20%




**Cover strip L110, plastic SOFT**  
(for curved elements)  
for balcony profile HM-20110 drilled Ø 2.0 mm

21049.20.W




Stock lengths of 2 m

Made-to-measure + 20%










**Profile connector V110, spring steel**

21220



**Side cap S20110, grey plastic**  
prevents the ingress of concrete water

21052.14

	Article description	Order no.
	<b>Aluminium nails 3.1 x 55 mm</b> Box contains 500 <i>Clous en aluminium 3,1 x 55 mm</i> <i>Cartons de 500 pcs</i>	<b>991105</b>
	<b>Double head pin</b>  1.6 x 24/ 35 mm  2.0 x 24/ 32 mm  2.0 x 24/ 32 mm, grooved	<b>991102</b>  <b>991106</b>  <b>991107</b>
	<b>Locking device C110, nickel-plated iron</b>	<b>25200</b>  50 pc.
	<b>Roller, metal, with clamping eyelet</b> for balcony profile HM-20110 and 20150  Plastic, grey  Plastic, white	<b>21210.14</b>  <b>21210.20</b>
	<b>Eyelet roller with rotating sewn eyelet</b> for balcony profile HM-20110 and 20150  Plastic, grey  Plastic, white	<b>21211.14</b>  <b>21211.20</b>
<b>Bending service</b>	<b>Plan view</b> (seen from above). State room side.   <b>Radii:</b> from 300 to 1000 mm  90° angle or angle of your choice   <b>Non-standard radii and angles as per sketch</b>	<b>95.20110.1</b>  <b>95.20110.4</b>